

OPC Series Portable Compressors



OPC 1300-5000

SPECIFICATIONS

COMPRESSOR

		OPC 1300		OPC 2000		OPC 2500		OPC 3000		OPC 5000		
OPERATING PRESSURE	bar	7	15	7	7	10	7	10	7	8,5	10	
	psi	100	215	100	100	145	100	145	100	123	145	
NOMINAL CAPACITY	m ³ /min	1,75	1,2	2,0	2,5	1,8	2,9	2,1	5,0	4,6	3,8	
	cfm	62	43	70	90	65	105	75	180	165	135	
SOUND LEVEL db (A) LWA		97		97	98		98		98			
NB AIR FILTERS		1		1	1		2		2			
COMPRESSOR OIL CIRCUIT L		4,5		6,5	6,5		6,5		15			
COMPRESSED AIR OUTPUTS		1 x G3/4"		2 x G1/2"	2 x G1/2"		2 x G1/2"		1" + 2 x G3/4"			

ENGINE

MODEL / TYPE	BRIGGS & STRATTON N VANGUARD 23HP	KUBOTA D1105 StageV	KUBOTA D1105 StageV	KUBOTA D1105 StageV	KUBOTA V1505-T
NB CYLINDERS	2	3	3	3	4
NOMINAL POWER kW - hp	17,2 - 23	13,0 - 17,4	17,5 - 23,5	18,5 - 24,8	31,2 - 41,8
FUEL TANK	6,5	24	24	24	80

DIMENSIONS

WEIGHT IN KG on axle - on frame	180 - 175	490 - 415	505 - 430	521 - 446	728 - 638
MAXIMUM LENGTH IN MM A - X	1200 - 1106	2888 - 1514	2888 - 1550	2888 - 1550	2900 - 1820
WIDTH IN MM B - Y	790 - 602	1185 - 750	1190 - 760	1190 - 760	1326 - 897
HEIGHT IN MM C - Z	790 - 660	1320 - 980	1290 - 890	1290 - 890	1425 - 1125

